

1

2

3

4

This document contains proprietary information and such information may not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	H.wei	12/7/06	12/7/06

1 Electrical


1.1 Impedence	50 Ω
1.2 Dielectric withstanding voltage	1000V(volts RMS)
1.3 Center contact resistance	$\leq 3\text{M}\Omega$
1.4 Outer contact resistance	$\leq 2\text{M}\Omega$
1.5 Insulation resistance:	$\geq 5000\text{M}\Omega$

2 Environmental&Mechanical


2.1 Temperature range	-55 $^{\circ}\text{C}$ ~155 $^{\circ}\text{C}$
2.2 RoHs Compliant	
2.3 Durability	>500 cycles

3 Materials&plating

3.1 Body:	Brass, Gold plated
3.2 Insulator:	Teflon
3.3 Contact Pin:	Bronze Gold plated
3.5 Washer:	Brass, Gold plated
3.6 Hex Nut:	Brass, Gold plated




Recommended
Mount Hole



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 12/07/06	TITLE: RF Coaxial Connector SMA Fmale bulkhead Right Angel Conn. For PCB						
ENGINEER: L.yu 12/07/06							
APPROVED: W.yi 12/07/06		 DIMENSION IN MILLIMETERS (mm)					
TOLERANCES UNLESS OTHERWISE SPECIFIED		PART NO:	HL-SMA-KYWHD17	SIZE:	SCALE:	SHEET:	REV:
X	±0.50			A4	N/A	1/1	A
.X	±0.20						
.XX	±0.10						
ANGLES	±1°						

1

2

3

4